

Specyfikacje



Eaton 194832

Eaton Moeller series xPole Home - HN/HN-HX MCB. HN, xPole Home, 1-pole, tripping characteristic: C, rated current I_n : 20 A, rated switching capacity IEC/EN 60898-1: 6 kA

General specifications

PRODUCT NAME	Eaton Moeller series xPole Home - HN/HN-HX MCB
CATALOG NUMBER	194832
EAN	9010238063167
PRODUCT LENGTH/DEPTH	85 mm
PRODUCT HEIGHT	73 mm
PRODUCT WIDTH	17.7 mm
PRODUCT WEIGHT	0.12 kg
COMPLIANCES	RoHS conform
MODEL CODE	HN-C20/1

Zdjęcie jest reprezentatywne



Powering Business Worldwide

Delivery program

- APPLICATION**
- Switchgear for residential and commercial applications
 - xPole Home - Switchgear for residential applications

NUMBER OF POLES Single-pole

NUMBER OF POLES (TOTAL) 1

NUMBER OF POLES (PROTECTED) 1

TRIPPING CHARACTERISTIC C

RELEASE CHARACTERISTIC C

AMPERAGE RATING 20 A

- TYPE**
- HN
 - Miniature circuit breaker

Technical Data - Mechanical

WIDTH IN NUMBER OF MODULAR SPACINGS 1

BUILT-IN DEPTH 44 mm

DEGREE OF PROTECTION IP20

CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MIN 1 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (SOLID-CORE) - MAX 25 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MIN 1 mm²

CONNECTABLE CONDUCTOR CROSS SECTION (MULTI-WIRED) - MAX 25 mm²

Technical Data - Electrical

VOLTAGE TYPE AC

RATED OPERATIONAL VOLTAGE (UE) - MAX 230 V

RATED INSULATION VOLTAGE (UI) 440 V

RATED IMPULSE WITHSTAND VOLTAGE (UIMP) 4 kV

FREQUENCY RATING - MIN 50 Hz

FREQUENCY RATING - MAX 60 Hz

RATED SWITCHING CAPACITY (IEC/EN 60898-1) 6 kA

OVERVOLTAGE CATEGORY III

POLLUTION DEGREE 3

Design verification as per IEC/EN 61439 - technical data

RATED OPERATIONAL CURRENT FOR SPECIFIED HEAT DISSIPATION (IN) 20 A

HEAT DISSIPATION PER POLE, CURRENT-DEPENDENT 0 W

EQUIPMENT HEAT DISSIPATION, CURRENT-DEPENDENT 3.2 W

STATIC HEAT DISSIPATION, NON-CURRENT-DEPENDENT 0 W

HEAT DISSIPATION CAPACITY 0 W

AMBIENT OPERATING TEMPERATURE - MIN -25 °C

AMBIENT OPERATING TEMPERATURE - MAX 75 °C

Design verification as per IEC/EN 61439

10.2.2 CORROSION RESISTANCE	Meets the product standard's requirements.
10.2.3.1 VERIFICATION OF THERMAL STABILITY OF ENCLOSURES	Meets the product standard's requirements.
10.2.3.2 VERIFICATION OF RESISTANCE OF INSULATING MATERIALS TO NORMAL HEAT	Meets the product standard's requirements.
10.2.3.3 RESIST. OF INSUL. MAT. TO ABNORMAL HEAT/FIRE BY INTERNAL ELECT. EFFECTS	Meets the product standard's requirements.
10.2.4 RESISTANCE TO ULTRA-VIOLET (UV) RADIATION	Meets the product standard's requirements.
10.2.5 LIFTING	Does not apply, since the entire switchgear needs to be evaluated.
10.2.6 MECHANICAL IMPACT	Does not apply, since the entire switchgear needs to be evaluated.
10.2.7 INSCRIPTIONS	Meets the product standard's requirements.
10.3 DEGREE OF PROTECTION OF ASSEMBLIES	Does not apply, since the entire switchgear needs to be evaluated.
10.4 CLEARANCES AND CREEPAGE DISTANCES	Meets the product standard's requirements.
10.5 PROTECTION AGAINST ELECTRIC SHOCK	Does not apply, since the entire switchgear needs to be evaluated.
10.6 INCORPORATION OF SWITCHING DEVICES AND COMPONENTS	Does not apply, since the entire switchgear needs to be evaluated.
10.7 INTERNAL ELECTRICAL CIRCUITS AND CONNECTIONS	Is the panel builder's responsibility.
10.8 CONNECTIONS FOR EXTERNAL CONDUCTORS	Is the panel builder's responsibility.
10.9.2 POWER-FREQUENCY ELECTRIC STRENGTH	Is the panel builder's responsibility.
10.9.3 IMPULSE WITHSTAND VOLTAGE	Is the panel builder's responsibility.
10.9.4 TESTING OF ENCLOSURES MADE OF INSULATING MATERIAL	Is the panel builder's responsibility.
10.10 TEMPERATURE RISE	The panel builder is responsible for the

Additional information

CURRENT LIMITING CLASS	3
FEATURES	Additional equipment possible
SPECIAL FEATURES	Ambient temperature hint: a 1 °C increase results in a 0.5% linear reduction of current carrying capacity
SUITABLE FOR	Flush-mounted installation
USED WITH	HN Miniature circuit breaker

	temperature rise calculation. Eaton will provide heat dissipation data for the devices.
10.11 SHORT-CIRCUIT RATING	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.12 ELECTROMAGNETIC COMPATIBILITY	Is the panel builder's responsibility. The specifications for the switchgear must be observed.
10.13 MECHANICAL FUNCTION	The device meets the requirements, provided the information in the instruction leaflet (IL) is observed.

Do pobrania

BROSZURY	eaton-xPole-home-leaflet-br003019en-en-gb.pdf
CERTYFIKATY	HN_EN.pdf
CHARACTERISTIC CURVE	eaton-xpole-mmc4-6-m-mcb-characteristic-curve-002.jpg eaton-xpole-mmc4-6-m-mcb-characteristic-curve-004.jpg
DEKLARACJE ZGODNOŚCI	eaton-mcb-declaration-of-conformity-eu250069en.pdf
KATALOGI	eaton-xpole%20home-hn-mcb-catalog-ca019020en-en-us.pdf
MODELE MCAD	eaton-non-selective-universal-mcb-mcad-drawings-faz-pls-1p.dwg pls_1p.stp
RYSUNKI	eaton-xpole-pl6-mcb-dimensions.jpg eaton-xpole-hnhn-hx-mcb-3d-drawing-002.jpg
SCHEMATY POŁĄCZEŃ	eaton-xpole-mmc4-6-m-mcb-wiring-diagram-002.jpg

NAZWA PROJEKTU:

NUMER PROJEKTU:

PRZYGOTOWANE PRZEZ:

DATA:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Irlandia
Eaton.com

© 2025 Eaton. Wszelkie prawa zastrzeżone.

Najnowsze informacje o produktach i wsparciu znajdują się na naszych mediach społecznościowych.

